



NOV213

Due to the strong growth of internet commerce, there has been a rapid increase in the use of small delivery vans for delivering packages in inner city areas. In most cases, these packages are very sensitive to handle. Furthermore, the huge variety of different delivery van shapes and sizes requires the seal between the van and the building to be highly versatile. The NOV213 satisfies these requirements perfectly.

Structure

- frame construction of pre-galvanized steel
- solid frame construction offers optimal positioning of the vertical cushions
- all cushions are coated with a durable synthetic fabric for optimum sealing and durability
- all cushions are made of a flexible foam material
- the roof structure has an integrated rain gutter

Material

- basic construction made of pre-galvanized steel and flexible foam material coated synthetic material
- the special finished side cushions are patented.
- flame retardant according to DIN 75200

Processing

- the outside of the cushions is black

Safety devices

- the shape and position of the cushions protect both the VS250 and the building against damage in the event of careless reversing
- white stripes (optional) on the top side cushions guide the driver

Requirements for in-site installation

- a stable, smooth wall or a stable subframe is required for mounting
- the sizes and free space as described in the technical datasheet must be observed
- if corrugated cladding is used, a flat recess made of smooth sheet metal covering must be created into which the NOV213 fits
- max. door opening (width x height) 1600 x 2500 mm

Standard dimensions (mm)

width	2170
height	3000
depth	810

Technical data

side curtain	0,5 mm
top curtain	0,7 mm
plastic material weight	580 g/m ²
tear resistance according to DIN 53363	3300/2500 (N/5 cm)
tensile strength according to DIN 53354	2300/2000 (N/5 cm)
temperature resistance	-30 °C/+70 °C
fire resistance	B1 flame retardant

Options/Accessoires

- different dimensions are available
- white vertical stripes on the top side cushions to guide the driver
- recesses for rear view cameras
- hand-operated loading ramp made of durable aluminium

